

Order code for explosion-proof heater **RIZUR-OShA-R**

Ordering information: **RIZUR-OShA-R-4-S-(+5)-T6-230-25-0-1-0**

1 2 3 4 5 6 7 8 9 10

1. Model	
RIZUR-OShA-R	Model of the heater
2. Capacity	
1	100 W
2	200 W
3	300 W
4	400 W
10	1000 W
15	1500 W
20	2000 W
X	Specify the required capacity (upon an agreement with the manufacturer)
3. Heater's design variants	
F	F-variant. Thermoregulator based on bimetallic thermostat. (page 25)
FT	FT-variant. Thermoregulator based on bimetallic thermostat. Please, also specify the order code for the thermoregulator RIZUR-TB-FT. (page 26)
S	S-variant. Thermoregulator based on digital controls. (page 27)
ST	ST-variant. Thermoregulator based on digital controls.
SR	SR-variant. Thermoregulator based on digital controls, with alarm signaling. Please, specify the order code for the thermoregulator RIZUR-TB-DCS. (page 29)
AR	AR-variant. Thermoregulator based on digital controls with local or remote controls and an emergency alarm. Please, specify the order code for the thermoregulator RIZUR-DCS-2. (see page 31)
4. Air temperature maintained	
-10	+10/+20°C (for F, FT design variants)
(X)	Specify the required temperature in the range of 40°C... +50°C (for S, ST, SR design variants)

5. Temperature rating	
T4	Temperature on the heater's surface is under +135°C
T5	Temperature on the heater's surface is under +100°C
T6	Temperature on the heater's surface is under +85°C
X	Specify the required temperature on the heater's surface (upon an agreement with the manufacturer)
6. Supply voltage	
230	230 V AC
24	24 V DC (upon an agreement with the manufacturer only)
380	380 V AC (upon an agreement with the manufacturer only)
X	Specify the required power supply voltage (upon an agreement with the manufacturer)
7. Cable length to thermoregulator, L2	
25	250 mm
30	300 mm
50	500 mm
X	Specify the required cable length
8. L2 cable protection with a metal hose	
0	Without a metal hose
M	With a metal hose
9. Cable length from the thermoregulator, L1 (only for the S- and F-variants)	
0	For the following heater design variants: FT, ST, SR, AR
1	1 m
2	2 m
3	3 m
X	Specify the required cable length
10. L1 cable protection with a metal hose	
0	Without a metal hose
M	With a metal hose