



000 «NPO RIZUR» www.rizur.ru +7 (4912) 20-20-80

## INQUIRY FORM Nº.

Soft enclosure RIZUR

Company name			
Name of the facility			
Contact person			
Phone/fax/e-mail			
Quantity of soft enclosures	pcs.		
Position tag			
Detail specifications of the equipment to be installed in RIZUR soft enclosure (specify the order code of the products, valve assemblies, etc.)			
Equipment dimensions, HxWxD	xmm  Please, provide a scheme of the equipment and specify:  1. Equipment dimensions 2. Heated areas 3. Location of glands (cable, pulse) and observation windows		
Maximum surface temperature of the heated equipment	°C		
Observation window	□ None	☐ Transparent observation window	☐ Transparent observation window with a through opening
Electric heating	□ None □ Self-regulating heating cable, 1ExellC T6T3GbX □ Heater RIZUR-OUR-PL, 1ExmbllC T3T6GbX		
Min. and max. ambient temperatures	fromtooC		
Temperature inside RIZUR soft enclosure during the heating process (Heating power is calculated individually depending on the enclosure's parameters)	Min°C Max°C  □ Output relay signals for decrease/increase in temp°C/°C		
Electrical connection	☐ to the customer's ☐ Junction box is supplied with the soft enclosure junction box		
	The length of the supply cable (to a junction box)mProtection of the power cable with a metal hose	Supply cable (to the junction box)m  Protection of the power cable with a metal hose Power cable parameters: Ø cablemm Ø armormm Ø metal hosemm	Fixation of a junction box on the soft enclosure  Protection of the power cable with a metal hose Power cable parameters: Ø cablemm Ø armormm Ø metal hosemm
Options for a soft enclosure	RIZUR soft enclosure for impulse tubes  Length of a soft enclosure (impulse tube) m  Diameter of an impulse tubemm  Maximum medium temperature of an impulse tube°C  Cleaning-up/steaming-out operation°C  Quantity of the impulse tubespcs  Pre-insulated tubing bundle RizurPak (please, attach an inquiry form for RizurPak)		
Additional information		or there're any other que	

please phone for an explanation +7 (4912) 20-20-80

8