



000 «NPO RIZUR» www.rizur.ru +7 (4912) 20-20-80

# INQUIRY FORM № \_\_\_\_\_

Technical regulations  
TU 26.5152-001-12189681-2018

## Bypass level gauge with a sight glass RIZUR-NBK-GLASS

Company name	
Contact person, position	
Contact details, tel., e-mail	
Number of level gauges, pcs.	
Operating medium	
Liquid density, kg/m <sup>3</sup>	
Viscosity, cP	
Process temperature/design temperature, °C	
Process pressure / design pressure, MPa	
Medium characteristics: aggressive to stainless steel	
Ambient temperature, °C	
Valve material	
Glass type	<input type="checkbox"/> Glass sight tube (execution only for RIZUR-NBK-GLASS-C) <input type="checkbox"/> Transparent type glass plate (execution only for RIZUR-NBK-GLASS-P) <input type="checkbox"/> Reflex type glass plate (execution only for RIZUR-NBK-GLASS-P) <input type="checkbox"/> Single color quartz glass (execution only for RIZUR-NBK-GLASS-K) <input type="checkbox"/> Bi-color quartz glass (execution only for RIZUR-NBK-GLASS-K) <input type="checkbox"/> Other version (specify execution and glass type)
Mounting type: - side mounting («side-side») - side mounting («remote side-side»)	
Process connection type: - welding pipe (specify DN) - thread (specify type) - flange (specify DN, PN and sealing surface)	
Distance between process connection centers, mm	
Measuring range, mm	
Scale (yes/no)	
Upper end of the chamber - a blind cap / with a valve / with a screw plug - a blind flange / with a valve / with a screw plug (please specify the connection size, thread type, flange facing)	
Lower end of the chamber - a blind cap / with a valve / with a screw plug - a blind flange / with a valve / with a screw plug (please specify the connection size, thread type, flange facing)	
Steam heating and insulation (please specify the connection size, thread type, flange facing)	
Electrically heated enclosure/soft enclosure (please specify the maintained temperature)	
Additional requirements	