

## Technical specifications

<b>Installation area</b>	<ul style="list-style-type: none"> <li>• General industrial areas</li> <li>• Explosion hazard zones V-1a and V-1g acc. to Electrical installation code (PUE)</li> </ul>
<b>Explosion protection marking</b>	1ExeIICT6...T3Gb
<b>Heating capacity</b>	30... 500 W
<b>Supply voltage</b>	230 (±15%) V
<b>Ingress protection</b>	0
<b>Warranty period</b>	24 months
<b>Average operation time</b>	Over 10 years

The dimensions of the heating sections depend on the heating section capacity. In order to receive the drawings with exact dimensions, please contact the OOO «NPO RIZUR» engineering department +7 (4912) 20-20-80, marketing@rizur.ru

## Order code for the heating section RIZUR

Ordering information: **RIZUR-100-1-T6-1-M**  
1 2 3 4 5 6

1. Design variant	
RIZUR	Design variant of the heating section
2. Heat capacity	
50	50 W
100	100 W
150	150 W
200	200 W
250	250 W
300	300 W
X	Please specify the required wattage of the heating section in W
3. Explosion protection	
0	General purpose industrial version
1	Explosion-proof version
4. Temperature class	
T4	Surface temperature is below 135°C
T5	Surface temperature is below 100°C
T6	Surface temperature is below 85°C
5. Power cable length	
1	1 m
2	2 m
3	3 m
X	Please specify the required cable length in meters
6. Metal hose protection for the cable	
0	None
M	Metal hose