

Order code for the safety shields for flange joints

RIZUR-F-KZ

Ordering information:

RIZUR-F-KZ-R-MN/15-N-165/80/130-2-3-0-200

1 2 3 4 5 6 7 8 9

1. Model	
RIZUR-F-KZ	Safety shield
2. Application	
Z	Heat insulation
R	Spillage protection
A	Unauthorized access protection (manufactured from perforated metals)
3. Design variants depending on the material used	
Textile	
TP	PVC-fabric
TS	Fiberglass with double-sided silicon coating
TF	Fiberglass with a fluoroplastic coating
TL	Polypropylene
TX	Other fabric (specified in writing outside the order code)
Metal	
__/XX	Choice of material
MN	Stainless steel (unpainted on default)*
MO	Zinc-plated steel(unpainted on default)*
MC	Carbon steel (with polymer powder coating and red color on default)*
MX	Other metal (specified in writing outside the order code)
* in case the product needs to be painted, color code RAL should be specified in writing outside the order code	
XX/__	Choice of thickness (for metal shields only)
12	Thickness of 1,2 mm
15	Thickness of 1,5 mm
20	Thickness of 2 mm
X	Other (specified in writing outside the order code)
Polymer materials	
PS	Fiberglass
PP	Polyethylene

4. Heat insulation	
U	Available (except for RIZUR-F-KZA)
N	Not available
5. Flange joint dimensions	
XX / __ / __	Specify the external diameter of a flange joint in mm, H
__ / XX / __	Specify the external diameter of the pipeline in mm, P
__ / __ / XX	Specify the width of a flange connection (with screws) in mm, L
* If both the safety shield and the pipeline have heat-insulation, then one should specify the external diameter and the distance from the screws to the coating. In case the flange joint is used for two tubes of different external diameters, then both should be specified, e.g. 150-129	
6. Safety shield type	
0	For non-metal shield
1	Type 1 - protection is installed only around the external diameter of the flange (without sides)
2	Type 2 - protection is installed around the external diameter and on the sides
7. Locking system	
V	Velcro strips
T	Tightening straps
S	Self-tightening lock
M	Metal clamp for use with screwdrivers
O	Holes for installing locks (standard design variant allows 3 locks to be installed)
XX	Other (specified in writing outside the order code)
Note: L or P versions can be used with textile shields only. Z or H variants can be used with metal shields only.	
8. Service openings	
0	Without openings
C	Drain adapter (for metal shields only)
9. Ambient temperature	
XX	Operating temperature, °C
10. Additional options	
C	The necessity of painting. Color code RAL should be specified in writing outside the order code.